

View Online at <https://aerobasegroup.com/nsn/5950-00-647-6874>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.938 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.094 inches

Body Width:

2.562 inches

Body Height:

3.625 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Voltage:

29.10 ac volts single component single secondary and 40.40 ac volts single component single secondary and 110.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0