

View Online at <https://aerobasegroup.com/nsn/5950-00-647-6987>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Transformer Function:

Line

Impedance Rating In Ohms:

600.0 single component single secondary

Frequency Rating:

300.0 hertz single component and 3.5 kilohertz single component

Maximum Transformer Power Rating:

10.0 decibels single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

Between 0.125 inches and 2.000 inches

Body Width:

Between 0.125 inches and 2.000 inches

Body Height:

Between 2.625 inches and 2.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0