

View Online at <https://aerobasegroup.com/nsn/5950-00-647-7057>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Impedance Rating In Ohms:

4000.0 single component single primary and 7000.0 single component single primary and 10000.0 single component single primary

Frequency Rating:

200.0 hertz single component and 10.0 kilohertz single component

Maximum Transformer Power Rating:

10.0 watts single component

Primary To Secondary Turn Ratio:

1 to 4-7/16 single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

2.750 inches

Body Width:

2.375 inches

Body Height:

3.812 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

30.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0