NSN 5950-00-647-7176

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-647-7176

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.875 inches single mounting facility single center group |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 1.90 henry single component single winding and 3.50 henry single component single winding |
| Body Length: |
| 2.625 inches |
| Body Width: |
| 2.500 inches |
| Body Height: |
| 3.500 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 15.0 milliamperes dc single component single winding and 165.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 29.000 single component single winding |
| Terminal Type And Quantity: |
| 2 standoff, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |