## NSN 5950-00-647-7183

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-7183

Parallel To Length:

Parallel To Width:

| Reliability Indicator:                                    |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities     |
| 2.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities     |
| 2.500 inches single mounting facility single center group |
| Inductance Type:  |
| Fixed   |
| Inductance Rating:  |
| 16.70 henry single component single winding               |
| Body Length:  |
| 3.375 inches  |
| Body Width:   |
| 3.125 inches  |
| Body Height:  |
| 4.250 inches  |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Hermetically sealed                                       |
| Mounting Facility Quantity:                               |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group                                |
| Rating Method:  |
| Electrical single component single winding                |
| Thready Qty Per Inch (tpi):                               |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group                                 |
| Winding Operating Current:                                |
| 90.0 milliamperes dc single component single winding      |
| Dc Resistance Rating In Ohms:                             |
| 110.000 single component single winding                   |
| Thread Series Designator:                                 |
| Unf single group  |
| Terminal Type And Quantity:                               |
| 2 standoff, solder lug                                    |
| Shelf Life:   |
| N/a   |

--

**Unit Of Measure:** 

## NSN 5950-00-647-7183

Reactor - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A058b0