## NSN 5950-00-647-7768

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-647-7768
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.125 inches single mounting facility single center group
Mounting Hole Diameter:
0.205 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
4.500 inches
Body Width:
4.250 inches
Body Height:
5.000 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
4.0 amperes ac single component single secondary
Special Features:
Primary winding tapped to give secondary voltages of 3.0 3.2 3.4 3.6 3.8 4.0 4.2 4.4 4.6 4.8 5.0
Terminal Type And Quantity:
15 standoff, solder lug and 1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

. .

A058b0