# NSN 5950-00-647-7885

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-7885

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.375 inches single mounting facility single center group

## **Overall Height:**

5.625 inches

## **Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

3.375 inches

### **Body Width:**

3.250 inches

## **Maximum Operating Temp:**

30.0 degrees celsius

## Inclosure Type:

Hermetically sealed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## **Winding Function And Quantity:**

1 primary single component and 3 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.164 inches single group

## **Winding Operating Current:**

3.25 amperes ac single component 3rd secondary

## **Winding Operating Voltage:**

6.30 ac volts single component 3rd secondary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

8 standoff, solder lug

## Shelf Life:

N/a

# **NSN 5950-00-647-7885**Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

No

Fiig:

A058b0