

View Online at <https://aerobasegroup.com/nsn/5950-00-647-7957>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.562 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Impedance Rating In Ohms:

12500.0 single component all secondary

Frequency Rating:

30.0 hertz single component and 15.0 kilohertz single component

Maximum Transformer Power Rating:

15.0 decibels single component

Primary To Secondary Turn Ratio:

1 to 1-6/10 single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.125 inches

Body Width:

2.000 inches

Body Height:

3.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

10.0 milliamperes dc single component all primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0