

View Online at <https://aerobasegroup.com/nsn/5950-00-647-8089>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.312 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.750 inches

Body Width:

3.750 inches

Body Height:

7.500 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

3.25 amperes ac single component 2nd secondary

Winding Operating Voltage:

70.00 ac volts single component all primary and 100.00 ac volts single component all primary

Special Features:

Secondary no. 2 is rated at 6.5 amp between the 0.5 v and 10.5 v taps

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0