

View Online at <https://aerobasegroup.com/nsn/5950-00-647-8182>

Reliability Indicator:

Not established

Overall Length:

2.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Overall Height:

4.125 inches

Overall Width:

2.750 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

60.0 milliamperes ac single component single secondary

Winding Operating Voltage:

117.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 standoff insulator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0