

View Online at <https://aerobasegroup.com/nsn/5950-00-647-8619>

Reliability Indicator:

Not established

Overall Length:

4.688 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility single center group

Overall Height:

7.250 inches

Overall Width:

4.062 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Height:

6.438 inches

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

90.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

45.00 ac volts single component 1st secondary and 995.00 ac volts single component 1st secondary and 1.04 ac kilovolts single component 1st secondary

Special Features:

Current drain between 45v tap and 995v tap is 0.032 amp

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0