## NSN 5950-00-647-9886

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-647-9886

| Reliability Indicator:  |
|---|
| Not established   |
| Turn Quantity:  |
| 65 single component single winding  |
| Inductance Rating:  |
| 30.00 microhenries single component single winding and 55.00 microhenries single component single winding |
| Coil Form Type:   |
| Hollow single component   |
| Core Construction:  |
| Powdered single component   |
| Body Length:  |
| 1.000 inches  |
| Body Outside Diameter:  |
| 0.367 inches  |
| Inclosure Type:   |
| Open  |
| Mounting Method:  |
| Threaded bushing single group   |
| Rating Method:  |
| Electrical single component single winding and winding turns single component single winding              |
| Thread Size:  |
| 0.190 inches single group   |
| Winding Conductor Size:   |
| 0.00562 inches american wire gage single component single winding   |
| Winding Operating Current:  |
| 125.0 milliamperes dc single component single winding   |
| Dc Resistance Rating In Ohms:   |
| 2.000 single component single winding   |
| Quality Factor:   |
| 40 single component single winding  |
| Adjustment Method And Quantity:   |
| 1 adjustable core single component  |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5950-00-647-9886

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0