

View Online at <https://aerobasegroup.com/nsn/5950-00-648-0207>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.781 inches

Body Width:

7.375 inches

Body Height:

8.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

1 primary and 1 secondary single component

Winding Operating Current:

170.0 milliamperes ac single component single secondary

Winding Operating Voltage:

4.00 ac kilovolts and 4.10 ac kilovolts and 4.20 ac kilovolts single component single secondary

Special Features:

Primary is tapped at 115 v ea tap to give alternate voltage in secondary

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0