

View Online at <https://aerobasegroup.com/nsn/5950-00-648-0207>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.000 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

6.781 inches

**Body Width:**

7.375 inches

**Body Height:**

8.000 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange and unthreaded hole single group

**Winding Function And Quantity:**

1 primary and 1 secondary single component

**Winding Operating Current:**

170.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

4.00 ac kilovolts and 4.10 ac kilovolts and 4.20 ac kilovolts single component single secondary

**Special Features:**

Primary is tapped at 115 v ea tap to give alternate voltage in secondary

**Terminal Type And Quantity:**

7 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0