## NSN 5950-00-648-0307

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-0307
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.312 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.688 inches single mounting facility single center group
Inductance Type:
Swinging
Inductance Rating:
7.00 henry single component single winding and 15.00 henry single component single winding
Body Length:
4.250 inches
Body Width:
3.625 inches
Body Height:
5.500 inches
Maximum Operating Temp:
125.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
20.0 milliamperes dc single component single winding and 390.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
90.000 single component single winding
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
2 standoff, solder lug
Shalf Life:

N/a

## NSN 5950-00-648-0307

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0