Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-0615

Not established Turn Quantiy: 14 single component all primary Inductance Rating: 1.00 microhenries single component all primary Frequency Rating: 30.0 megahertz single component Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Longth: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding Function And Quantity: 2 primary single component Inread Stae: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Streis Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life: Nra Unit Of Measure:	Reli	iability Indicator:
14 single component all primary Inductance Rating: 1.00 microhenries single component all primary Frequency Rating: 30.0 megahertz single component Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mouning Method: Threade bushing single group Rating Method: Winding furms single component all primary and electrical single component all primary Yinding Function And Quantity: 2 primary single component Thread Size: 0.190 inches single group Winding Conductor Size: 0.190 inches single component Adjustment Method And Quantity: 1 adjustable core single component Thread Size 0.190 inches single group Thread Size 0.190 inches single group Thread Size 0.190 inches single component Thread Size 1 adjustable core single compo	Not	established
Inductance Rating: 1.00 microhenries single component all primary Frequency Rating: 30.0 megahertz single component Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life: N/a Unit Of Measure: -	Tur	n Quantity:
.1.00 microhenries single component all primary Frequency Rating: 30.0 megahertz single component Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding function And Quantity: 2 primary single component Thread Size: 0.0795 inches samerican wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: Na	14 s	single component all primary
Frequency Rating: 30.0 megahertz single component Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding function And Quantity: 2 primary single component Thread Size: 0.190 inches single group Minding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: -	Ind	uctance Rating:
30.0 megahertz single component Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: -	1.00) microhenries single component all primary
Coil Form Type: Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threade bushing single group Rating Method: Winding function And Quantity: 2 primary single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thread Yap Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: -	Fre	quency Rating:
Hollow single component Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life: N/a Unit Of Measure:	30.0) megahertz single component
Adjustment Device Drive Type: Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: -	Coi	I Form Type:
Shaft single component Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.100 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life: N/a Unit Of Measure:	Holl	low single component
Body Length: 1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Adj	ustment Device Drive Type:
1.120 inches Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding function And Quantity: 2 primary single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life: N/a Unit Of Measure: 	Sha	Ift single component
Body Outside Diameter: 0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Sheff Life: N/a Unit Of Measure: 	Boo	dy Length:
0.250 inches Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: 	1.12	20 inches
Inclosure Type: Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Boo	dy Outside Diameter:
Fully enclosed Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Shelf Life: N/a Unit Of Measure:	0.25	50 inches
Mounting Method: Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Incl	losure Type:
Threaded bushing single group Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Shelf Life: N/a Unit Of Measure:	Full	y enclosed
Rating Method: Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Μοι	unting Method:
Winding turns single component all primary and electrical single component all prima Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Thre	eaded bushing single group
Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Rat	ing Method:
2 primary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Win	ding turns single component all primary and electrical single component all primar
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Win	iding Function And Quantity:
32 single group Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	2 pr	imary single component
Thread Size: 0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Thr	eady Qty Per Inch (tpi):
0.190 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	32 s	single group
Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Thr	ead Size:
0.00795 inches american wire gage single component all primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	0.19	90 inches single group
Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Win	nding Conductor Size:
1 adjustable core single component Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	0.00	0795 inches american wire gage single component all primary
Thread Series Designator: Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Adj	ustment Method And Quantity:
Unf single group Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	1 ac	djustable core single component
Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Thr	ead Series Designator:
4 tab, solder lug Shelf Life: N/a Unit Of Measure:	Unf	single group
Shelf Life: N/a Unit Of Measure:	Ter	minal Type And Quantity:
N/a Unit Of Measure:	4 ta	b, solder lug
Unit Of Measure:	She	elf Life:
	N/a	
	Uni	t Of Measure:
Demilitarization:		
	Den	nilitarization:

NSN 5950-00-648-0615

Radio Frequency Transformer - Page 2 of 2

Fiig: A058b0

