NSN 5950-00-648-0624

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-0624

Reliability Indicator:
Not established
Inductance Rating:
340.00 microhenries single component single secondary
Frequency Rating:
400.0 kilohertz single component
Coil Form Type:
Hollow single component
Adjustment Device Drive Type:
Shaft single component
Body Length:
2.000 inches
Body Width:
1.630 inches
Body Height:
0.890 inches
Distance Between Mounting Facility Centers:
1.000 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Rating Method:
Rating Method: Electrical single component single secondary
Electrical single component single secondary
Electrical single component single secondary Winding Function And Quantity:
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi):
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size:
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size:
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size: 0.00397 inches american wire gage single component single primary
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size: 0.00397 inches american wire gage single component single primary Adjustment Method And Quantity:
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size: 0.00397 inches american wire gage single component single primary Adjustment Method And Quantity: 1 adjustable core single component
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size: 0.00397 inches american wire gage single component single primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator:
Electrical single component single secondary Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size: 0.00397 inches american wire gage single component single primary Adjustment Method And Quantity: 1 adjustable core single component Thread Series Designator: Unc single group

N/a

NSN 5950-00-648-0624

Radio Frequency Transformer - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0