## NSN 5950-00-648-0714



Radio Frequency Transformer - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5950-00-648-0714 **Reliability Indicator:** Not established **Inductance Rating:** 41.00 microhenries single component single primary and 6.20 millihenries single component single primary Frequency Rating: 120.0 kilohertz single component **Coil Form Type:** Hollow single component **Adjustment Device Drive Type:** Slotted screw single component **Body Length:** 1.438 inches **Body Width:** 1.438 inches **Body Height:** 1.750 inches **Distance Between Mounting Facility Centers:** 1.375 inches single mounting facility single center group **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 2 single group **Mounting Method:** Threaded stud single group **Rating Method:** Electrical single component single primary **Winding Function And Quantity:** 1 primary single component Thready Qty Per Inch (tpi): 40 single group **Thread Size:** 0.112 inches single group **Adjustment Method And Quantity:** 1 adjustable core single component **Thread Series Designator:** 

Unc single group

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5950-00-648-0714

Radio Frequency Transformer - Page 2 of 2



| _                |      | •• | • • |     |     |        |   |  |
|------------------|------|----|-----|-----|-----|--------|---|--|
| וו               | em   | ш  | 112 | r17 | 2+  | $\sim$ | n |  |
| $\boldsymbol{-}$ | CIII | •• | ıιa | 114 | .aı | ı      |   |  |

No

Fiig:

A058b0