## NSN 5950-00-648-1090

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-1090

| Reliability Indicator:   |
|--|
| Not established  |
| Turn Quantity:   |
| 33 single component all primary  |
| Inductance Rating:   |
| 5.50 microhenries single component all primary   |
| Frequency Rating:  |
| 5.0 megahertz single component   |
| Coil Form Type:  |
| Hollow single component  |
| Adjustment Device Drive Type:  |
| Slotted screw single component   |
| Body Length:   |
| 2.780 inches   |
| Body Width:  |
| 1.080 inches   |
| Body Height:   |
| 0.920 inches   |
| Distance Between Mounting Facility Centers:  |
| 0.969 inches single mounting facility single center group                              |
| Inclosure Type:  |
| Open   |
| Mounting Facility Quantity:  |
| 2 single group   |
| Mounting Method:   |
| Threaded stud single group   |
| Rating Method:   |
| Electrical single component all primary and winding turns single component all primary |
| Winding Function And Quantity:   |
| 2 primary single component   |
| Thready Qty Per Inch (tpi):  |
| 40 single group  |
| Thread Size:   |
| 0.112 inches single group  |
| Winding Conductor Size:  |
| 0.00795 inches american wire gage single component all primary                         |
| Adjustment Method And Quantity:  |
| 2 adjustable core single component   |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 4 tab, solder lug  |

## NSN 5950-00-648-1090

Radio Frequency Transformer - Page 2 of 2



| Sh | elf | Life: |
|----|-----|-------|
|    |     |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0