## NSN 5950-00-648-1092

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-1092

Reliability Indicator:
Not established
Turn Quantity:
6-1/2 single component all primary
Inductance Rating:
0.66 microhenries single component all primary
Frequency Rating:
27.5 megahertz single component
Coil Form Type:
Hollow single component
Adjustment Device Drive Type:
Slotted screw single component
Body Length:
2.780 inches
Body Width:
1.080 inches
Body Height:
0.920 inches
Distance Between Mounting Facility Centers:
0.969 inches single mounting facility single center group
In all assess Trees as
Inclosure Type:
Open
Open
Open  Mounting Facility Quantity:
Open  Mounting Facility Quantity: 2 single group
Open  Mounting Facility Quantity: 2 single group  Mounting Method:
Open  Mounting Facility Quantity: 2 single group  Mounting Method: Threaded stud single group
Open  Mounting Facility Quantity: 2 single group  Mounting Method: Threaded stud single group  Rating Method:
Open  Mounting Facility Quantity:  2 single group  Mounting Method:  Threaded stud single group  Rating Method:  Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity:  2 primary single component
Open  Mounting Facility Quantity:  2 single group  Mounting Method:  Threaded stud single group  Rating Method:  Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity:
Open  Mounting Facility Quantity:  2 single group  Mounting Method:  Threaded stud single group  Rating Method:  Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity:  2 primary single component
Open  Mounting Facility Quantity: 2 single group  Mounting Method: Threaded stud single group  Rating Method: Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity: 2 primary single component  Thready Qty Per Inch (tpi):
Open  Mounting Facility Quantity:  2 single group  Mounting Method:  Threaded stud single group  Rating Method:  Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity:  2 primary single component  Thready Qty Per Inch (tpi):  40 single group
Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component all primary and winding turns single component all primary Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 40 single group Thread Size:
Mounting Facility Quantity:  2 single group  Mounting Method: Threaded stud single group  Rating Method: Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity: 2 primary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group
Mounting Facility Quantity:  2 single group  Mounting Method: Threaded stud single group  Rating Method: Electrical single component all primary and winding turns single component all primary Winding Function And Quantity: 2 primary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Conductor Size: 0.00795 inches american wire gage single component all primary Adjustment Method And Quantity:
Mounting Facility Quantity:  2 single group  Mounting Method: Threaded stud single group  Rating Method: Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity: 2 primary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group  Winding Conductor Size: 0.00795 inches american wire gage single component all primary  Adjustment Method And Quantity: 2 adjustable core single component
Open  Mounting Facility Quantity:  2 single group  Mounting Method:  Threaded stud single group  Rating Method:  Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity:  2 primary single component  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.112 inches single group  Winding Conductor Size:  0.00795 inches american wire gage single component all primary  Adjustment Method And Quantity:  2 adjustable core single component  Thread Series Designator:
Mounting Facility Quantity:  2 single group  Mounting Method: Threaded stud single group  Rating Method: Electrical single component all primary and winding turns single component all primary  Winding Function And Quantity: 2 primary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group  Winding Conductor Size: 0.00795 inches american wire gage single component all primary  Adjustment Method And Quantity: 2 adjustable core single component

4 tab, solder lug

## NSN 5950-00-648-1092

Radio Frequency Transformer - Page 2 of 2



Sh	elf	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0