NSN 5950-00-648-1093

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-1093

The Common at the polytractor and a control of the
Reliability Indicator:
Not established
Turn Quantity:
19 single component all primary
Inductance Rating:
2.80 microhenries single component all primary
Frequency Rating:
9.2 megahertz single component
Coil Form Type:
Hollow single component
Adjustment Device Drive Type:
Slotted screw single component
Body Length:
2.780 inches
Body Width:
1.080 inches
Body Height:
0.920 inches
Distance Between Mounting Facility Centers:
0.969 inches single mounting facility single center group
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component all primary and winding turns single component all primary
Winding Function And Quantity:
2 primary single component
Thready Qty Per Inch (tpi):
40 single group
Thread Size:
0.112 inches single group
Winding Conductor Size:
0.00795 inches american wire gage single component all primary
Adjustment Method And Quantity:
2 adjustable core single component
Thread Series Designator:
Unc single group
Terminal Type And Quantity:

4 tab, solder lug

NSN 5950-00-648-1093

Radio Frequency Transformer - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0