

View Online at <https://aerobasegroup.com/nsn/5950-00-648-1542>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.6 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

3.094 inches

Body Width:

2.500 inches

Body Height:

3.031 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

3.6 amperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

1primary; 9 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0