NSN 5950-00-648-1626

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-1626

Note established Turn Quantity: 15200 single component single winding Body Length: 2.250 inches Body Outside Diameter: 2.000 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
15200 single component single winding Body Length: 2.250 inches Body Outside Diameter: 2.000 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Body Length: 2.250 inches Body Outside Diameter: 2.000 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
2.250 inches Body Outside Diameter: 2.000 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Body Outside Diameter: 2.000 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
2.000 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
1 single component Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Inclosure Type: Fully enclosed Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Mounting Method: Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Terminal single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
0.00795 inches american wire gage single component single winding Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Winding Operating Current: 120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
120.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Dc Resistance Rating In Ohms: 955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
955.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
2 wire lead Shelf Life: N/a
Shelf Life: N/a
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0