

View Online at <https://aerobasegroup.com/nsn/5950-00-648-1737>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

4.562 inches

**Body Width:**

4.125 inches

**Body Height:**

5.312 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Special Features:**

1 case metal material, moisture resistance and insulated per mil-t-27, grade 1, class a, primary winding 117 v rating, secondary windings rated 5 v at 3 amp, 6.3 v at 600 ma, 6.3 v at 3 amp, 6.3 v at 3 amp, 6.3 v at 7.5 amp, 880 v at 200 ma w/center tap

**Terminal Type And Quantity:**

15 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0