NSN 5950-00-648-1793

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-1793

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.062 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.062 inches single mounting facility single center group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.812 inches |
| Body Width: |
| 2.812 inches |
| Body Height: |
| 3.500 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Winding Operating Current: |
| 600.0 milliamperes dc single component 2nd secondary |
| Winding Operating Voltage: |
| 6.30 ac pounds per hour wet single component 2nd secondary |
| Special Features: |
| Case metal material |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| 40501.0 |

A058b0