NSN 5950-00-648-2049

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-2049

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

5.00 henry single component single winding

Frequency Rating:

60.0 hertz single component

Body Length:

2.375 inches

Body Width:

2.500 inches

Body Height:

3.250 inches

Maximum Operating Temp:

105.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

130.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

115.000 single component single winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 tab, solder lug

NSN 5950-00-648-2049

Reactor - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0