

View Online at <https://aerobasegroup.com/nsn/5950-00-648-2281>

**Reliability Indicator:**

Not established

**Transformer Function:**

Line

**Impedance Rating In Ohms:**

600.0 single component single secondary

**Frequency Rating:**

200.0 hertz single component and 50.0 kilohertz single component

**Maximum Transformer Power Rating:**

39.0 decibels single component

**Primary To Secondary Turn Ratio:**

1 to1-9/32 single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 1.370 inches and 1.380 inches

**Body Width:**

Between 0.901 inches and 0.911 inches

**Body Height:**

Between 1.995 inches and 2.005 inches

**Distance Between Mounting Facility Centers:**

0.625 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0