## NSN 5950-00-648-2469

Saturable Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-2469

| view Offiline at https://acrobasegroup.com/hsh/3330-00-040-2403           |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.500 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 9.000 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Body Length:  |
| 11.469 inches   |
| Body Width:   |
| 10.000 inches   |
| Body Height:  |
| 10.000 inches   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 6 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 2 primary and 2 control single component                                  |
| Saturation Current Rating:  |
| 400.0 milliamperes  |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group   |
| Dc Resistance Rating In Ohms:   |
| 3.400 single component all control  |
| Winding Operating Voltage:  |
| 206.00 ac volts single component all primary                              |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 8 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## **NSN 5950-00-648-2469** Saturable Reactor - Page 2 of 2



Fiig:

A058b0