## NSN 5950-00-648-2582

Reactor - Page 1 of 1

A058b0



| view Online at https://aerobasegroup.com/nsn/5950-00-646-2562  |
|--|
| Reliability Indicator:   |
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                                  |
| 2.500 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                   |
| 2.875 inches single mounting facility single center group  |
| Mounting Slot Width:   |
| 0.188 inches single group  |
| Inductance Type:   |
| Swinging   |
| Inductance Rating:   |
| 50.00 millihenries single component single winding and 530.00 millihenries single component single winding |
| Body Length:   |
| Between 3.500 inches and 3.850 inches  |
| Body Width:  |
| 3.062 inches   |
| Body Height:   |
| 2.750 inches   |
| Winding Quantity:  |
| 1 single component   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Flange single group and slot single group  |
| Rating Method:   |
| Electrical single component single winding   |
| Winding Operating Current:   |
| 3.0 amperes dc single component single winding   |
| Dc Resistance Rating In Ohms:  |
| 1.000 single component single winding  |
| Terminal Type And Quantity:  |
| 2 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |