NSN 5950-00-648-2775

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-2775

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.378 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.351 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| Body Length: |
| 3.379 inches |
| Body Width: |
| 3.118 inches |
| Body Height: |
| 2.100 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary and 2 control single component |
| Dc Resistance Rating In Ohms: |
| 5575.000 single component all control |
| Winding Operating Voltage: |
| 115.00 ac volts single component single primary |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |