NSN 5950-00-648-2922

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-2922

| · |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.188 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.156 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.969 inches |
| Body Width: |
| 2.625 inches |
| Body Height: |
| 2.375 inches |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 2.5 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 6.00 ac pounds per hour wet single component single secondary |
| Terminal Type And Quantity: |
| 4 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A058b0