

View Online at <https://aerobasegroup.com/nsn/5950-00-648-3936>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.500 inches

Body Width:

2.375 inches

Body Height:

3.125 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

4.2 amperes ac single component single secondary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0