NSN 5950-00-648-3980

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-3980

| Reliability Indicator: |
|---|
| Not established |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 2.219 inches |
| Body Outside Diameter: |
| 1.562 inches |
| Distance Between Mounting Facility Centers: |
| 1.812 inches single mounting facility single center group |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 6.0 milliamperes ac single component 3rd secondary |
| Winding Operating Voltage: |
| 48.00 ac volts single component 3rd secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 9 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Unit Of Measure. |
| Demilitarization: |
| |
| No |
| Filg: |
| A058b0 |
| |