# NSN 5950-00-648-4000

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-4000

## Reliability Indicator: Not established Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length:

1.750 inches

**Body Width:** 

1.625 inches

**Body Height:** 

2.219 inches

#### **Distance Between Mounting Facility Centers:**

1.440 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

**Mounting Facility Quantity:** 

2 single group

Mounting Method:

Threaded hole single group

#### Winding Function And Quantity:

1 primary single component and 2 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

#### Winding Operating Current:

24.0 milliamperes ac single component 2nd secondary

#### Winding Operating Voltage:

60.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

# NSN 5950-00-648-4000

Power Transformer - Page 2 of 2

**Fiig:** A058b0

