NSN 5950-00-648-4178

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-4178

Reliability Indicator:
Not established
Turn Quantity:
1220 single component single winding
Mounting Hole Diameter:
0.250 inches single group
Core Construction:
Powdered single component
Body Length:
2.250 inches
Body Width:
0.750 inches
Body Height:
3.062 inches
Distance Between Mounting Facility Centers:
2.000 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
2 single group Mounting Method:
Mounting Method:
Mounting Method: Unthreaded hole single group
Mounting Method: Unthreaded hole single group Rating Method:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 tab, solder lug
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.02535 inches american wire gage single component single winding Winding Operating Voltage: 440.00 ac pounds per hour wet single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: