

View Online at <https://aerobasegroup.com/nsn/5950-00-648-4337>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.500 inches

Body Width:

2.813 inches

Body Height:

2.375 inches

End Application:

Arsr-1, ca-4013 trigger amplifier

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Special Features:

6.3 v at 1 amp sec no. 1, 6.3 v at 1 amp sec no. 2; reference data, t-152, instruction book, arsr-1d/e/f, vol 5, sec 10, pg 10-46

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0