

View Online at <https://aerobasegroup.com/nsn/5950-00-648-4337>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

3.500 inches

**Body Width:**

2.813 inches

**Body Height:**

2.375 inches

**End Application:**

Arsr-1, ca-4013 trigger amplifier

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

1.0 amperes ac single component 3rd secondary

**Winding Operating Voltage:**

6.30 ac volts single component all secondary

**Special Features:**

6.3 v at 1 amp sec no. 1, 6.3 v at 1 amp sec no. 2; reference data, t-152, instruction book, arsr-1d/e/f, vol 5, sec 10, pg 10-46

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0