

View Online at <https://aerobasegroup.com/nsn/5950-00-648-4532>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Frequency Rating:

48.0 hertz single component and 62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 6.995 inches and 7.005 inches

Body Width:

Between 6.120 inches and 6.130 inches

Body Height:

Between 5.120 inches and 5.130 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

225.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 3rd secondary

Special Features:

1primary winding; 6secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

24 tab, solder lug and 3 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0