

View Online at <https://aerobasegroup.com/nsn/5950-00-648-4636>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.312 inches

Body Width:

2.000 inches

Body Height:

1.938 inches

Distance Between Mounting Facility Centers:

2.812 inches single mounting facility single center group

End Application:

Low pressure (lp) dry air-dehydrators, oliver perry class ffg, austin ship class lpd-4 amphibious transport docks, supply class aoe, blue ridge class aoe, blue ridge class lcc-19, milstar system, nimitz class cvn, I.P. Compressors, aircraft, c-2a (reprocured)

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.0 amperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

5.00 ac volts single component single secondary

Special Features:

Weapons system essential

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0