NSN 5950-00-648-4669Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-4669
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
3.875 inches
Body Width:
2.875 inches
Body Height:
2.625 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
12.0 amperes dc single component single secondary
Winding Operating Voltage:
6.30 ac pounds per hour wet single component single secondary
Special Features:
Case metal material; 0.875 in. O/a h of terminals
Terminal Type And Quantity:
4 standoff, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A058b0