## NSN 5950-00-648-4670

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-4670

| view Online at https://aerobasegroup.com/nsi//5550-00-040-4070                |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:     |
| 1.812 inches single mounting facility single center group                     |
| Center To Center Distance Between Mounting Facilities Parallel To Width:      |
| 1.625 inches single mounting facility single center group                     |
| Mounting Hole Diameter:   |
| 0.165 inches single group   |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                                 |
| Winding Shielding Method:   |
| Internal shield grounded to core and brought out to terminal single component |
| Body Length:  |
| 2.438 inches  |
| Body Width:   |
| 2.188 inches  |
| Body Height:  |
| 2.625 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                          |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component                   |
| Winding Operating Voltage:  |
| 5.00 ac volts single component single primary                                 |
| Terminal Type And Quantity:   |
| 5 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |

A058b0