NSN 5950-00-648-4904

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-4904

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.438 inches

Body Width:

2.125 inches

Body Height:

2.062 inches

Maximum Operating Temp:

180.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

220.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

776.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-648-4904Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A058b0