## NSN 5950-00-648-4946

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-4946

eliability Indicator:
ot established
enter To Center Distance Between Mounting Facilities Parallel To Length
.250 inches single mounting facility single center group
enter To Center Distance Between Mounting Facilities Parallel To Width:
125 inches single mounting facility single center group
requency Rating:
0.0 hertz single component and 1.0 kilohertz single component
aput-output Phase Relationship:
ingle phase to single phase single component
/inding Shielding Method:
iternal shield grounded to inclosure single component
ody Length:
000 inches
ody Width:
870 inches
ody Height:
.000 inches
iclosure Type:
ermetically sealed
lounting Facility Quantity:
single group
lounting Method:
hreaded hole single group
/inding Function And Quantity:
primary single component and 1 secondary single component
hready Qty Per Inch (tpi):
2 single group
hread Size:
190 inches single group
/inding Operating Current:
0 amperes ac single component single secondary
/inding Operating Voltage:
30 ac volts single component single secondary
hread Series Designator:
nf single group
erminal Type And Quantity:
tab, solder lug
helf Life:
/a
nit Of Measure:

## NSN 5950-00-648-4946

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

