

View Online at <https://aerobasegroup.com/nsn/5950-00-648-5136>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.562 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.062 inches

Body Width:

3.500 inches

Body Height:

5.250 inches

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

750.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Special Features:

1 primary, 6 secondaries

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0