

View Online at <https://aerobasegroup.com/nsn/5950-00-648-5341>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.281 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.188 inches

Body Width:

1.781 inches

Body Height:

2.250 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

9.5 amperes ac single component single secondary

Winding Operating Voltage:

2.50 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0