# NSN 5950-00-648-5348

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-5348

Reliability	Indicator:
Not establis	shad

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

# Frequency Rating:

400.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# Winding Shielding Method:

Internal shield grounded to inclosure single component

**Body Length:** 

2.875 inches

Body Width:

2.625 inches

**Body Height:** 

3.875 inches

Inclosure Type:

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 3 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# Thread Size:

0.164 inches single group

# **Winding Operating Current:**

600.0 milliamperes ac single component 3rd secondary

# **Winding Operating Voltage:**

6.30 ac volts single component all secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

8 standoff, solder lug

# Shelf Life:

N/a

# **Unit Of Measure:**

--

# NSN 5950-00-648-5348

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0