NSN 5950-00-648-5619

Vibrator Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-648-5619

| Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.688 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.438 inches single mounting facility single center group Body Length: |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: 1.688 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.438 inches single mounting facility single center group |
| 1.688 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.438 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: 1.438 inches single mounting facility single center group |
| 1.438 inches single mounting facility single center group |
| |
| Body Length: |
| |
| 2.250 inches |
| Body Width: |
| 2.000 inches |
| Body Height: |
| 3.156 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 50.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 29.00 dc volts single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A058b0