

View Online at <https://aerobasegroup.com/nsn/5950-00-648-5841>

Reliability Indicator:

Not established

Overall Length:

8.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.500 inches single mounting facility single center group

Overall Height:

9.562 inches

Overall Width:

7.375 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Height:

9.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

18 single group

Thread Size:

0.312 inches single group

Winding Operating Current:

12.0 amperes ac single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary and 16.50 ac volts single component single secondary and 28.00 ac volts single component single secondary and 39.00 ac volts single component single secondary and 50.50 ac volts single component single secondary and 61.00 ac volts single component single secondary and 73.00 ac volts single component single secondary and 84.50 ac volts single component single secondary and 95.50 ac volts single component single secondary and 107.00 ac volts single component single secondary and 118.00 ac volts single component single secondary and 119.50 ac volts single component single secondary and 120.50 ac volts single component single secondary and 122.00 ac volts single component single secondary and 123.00 ac volts single component single secondary and 124.00 ac volts single component single secondary and 125.00 ac volts single component single secondary and 126.00 ac volts single component single secondary and 127.00 ac volts single component single secondary and 128.00 ac volts single component single secondary and 129.50 ac volts single component single secondary

Thread Series Designator:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0