

View Online at <https://aerobasegroup.com/nsn/5950-00-648-6125>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.016 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.875 inches

Body Width:

2.781 inches

Body Height:

3.344 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 8 primary single component

Special Features:

Case metal material, 0.375 in. O/a h of terminals, primary winding 115 v rating, secondary windings rated 6.3 v at 200 ma, 6.3 v at 900 ma, 6.3 v at 900 ma, 6.3 v at 2.2 amp w/center tap, 25 v at 20 ma, 90 v at 300 ma, 500 v at 30 ma w/center tap, 600 v at 25 ma w/center tap

Terminal Type And Quantity:

21 standoff, solder lug

Specification Or Standard:

1 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0