## NSN 5950-00-648-6133

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-648-6133

Reliability	y Indicator:
Not estab	lished
Center To	Center Distance Between Mounting Facilities Parallel To Length:
4.375 inch	nes single mounting facility single center group
Center To	Center Distance Between Mounting Facilities Parallel To Width:
3.500 incl	nes single mounting facility single center group
Frequenc	ey Rating:
50.0 hertz	single component or 60.0 hertz single component
Input-out	put Phase Relationship:
Single pha	ase to single phase single component
Body Ler	ngth:
5.875 incł	nes
Body Wic	ith:
4.750 incł	nes
Body Hei	ght:
6.750 incł	nes
Inclosure	туре:
Hermetica	ally sealed
Mounting	Facility Quantity:
4 single g	roup
Mounting	Method:
Threaded	stud single group
Winding	Function And Quantity:
1 primary	single component and 3 secondary single component
Thready	Qty Per Inch (tpi):
20 single	group
Thread S	ize:
0.250 incł	nes single group
Winding	Operating Current:
7.0 ampei	res ac single component 1st secondary
Winding	Operating Voltage:
800.00 ac	volts single component 2nd secondary
Thread S	eries Designator:
Unc single	e group
Terminal	Type And Quantity:
10 tab, so	older lug
Shelf Life	:
N/a	
Unit Of M	leasure:
Demilitar	ization:
No	

## NSN 5950-00-648-6133

Power Transformer - Page 2 of 2

**Fiig:** A058b0

